



# CLEANING INSTRUCTIONS

## Light Granite Composite Sinks

Alpina | Chroma | Sand

### TO DEEP CLEAN YOUR LIGHT CRYSTALLITE SERIES SINK, PLEASE PROCEED AS FOLLOWS:

**Degrease:** Pour plenty of water and a little washing liquid onto a soft dishwashing sponge (without a scrubbing pad) or an eraser sponge and wipe over the sink in a circular motion. Rinse with plenty of clean water and then dry the sink with a soft microfiber cloth.

**Descale:** To remove stubborn limescale deposits, soap residue or gray haze, apply any mild descaler evenly to the affected surface and leave to work for 15 minutes. Then rinse with clean water and wipe dry. Repeat for stubborn limescale deposits.

**Metal Abrasion:** Remove metal abrasion residues from pans and baking trays and other stubborn stains with a moistened magic eraser sponge. Move the sponge in circular movement and with light pressure over the stain. Rinse with clear water.

**Brightening:** To brighten your sink and remove all remaining stains, bacteria and germs, fill your sink with warm water to a height of approx. 2 cm. Add 30 ml of a commercially available chlorine or hydrogen-based bleaching agent. Leave to work for 25 minutes. Then drain the water and rinse with plenty of fresh water. Wipe the sink with a dry, soft cloth and leave to dry for approx. 30 minutes. Repeat the process for stubborn stains. Protect your hands and eyes when using bleach.

**Deep Clean:** Pour approx. two centimeters of hot water (approx. 140°F) into the sink. Add one dishwasher tab or 2 tablespoons of a standard household dishwashing detergent to the hot water and stir well until the tab is clearly dissolved (caution: risk of scalding). You can apply a generous amount of the cleaning solution to the draining board or the edge of the sink using a dishwashing brush. Allow the lye to run off after 90 minutes and rinse the entire surface with plenty of cold water. If necessary, use the damp eraser sponge to remove any remaining residue. Then rinse well again, wipe the sink with a dry, soft cloth and leave to dry for at least 30 minutes.

**Sealing:** The sink must be completely clean and dry before sealing. Cover the parts not to be treated with a film and apply a sealant (approved for kitchen and bathroom sinks) as thinly and evenly as possible. It is best to apply a small amount of sealant to the surfaces to be treated and spread carefully with a clean fleece or microfiber cloth. After 1 minute, remove any excess sealant with a dry fleece or microfiber cloth. The product must be completely absorbed, it must not come to a standstill on the surface. The freshly treated sink should be protected from moisture for at least 6 hours, after which it is ready for use again.

**Please do not use any highly abrasive cleaning agents such as scouring agents, chlorine-based cleaners, drain cleaners or alkaline solutions and other solvents - these can cause lasting damage to your sink. You can easily keep your Pelican sink hygienically clean and remove even stubborn stains with mild cleaning and care products.**



# CLEANING INSTRUCTIONS

## Dark Granite Composite Sinks

Onyx | Gunmetal | Mocha | Concrete

### TO DEEP CLEAN YOUR DARK CRYSTALLITE SERIES SINK, PLEASE PROCEED AS FOLLOWS:

**Degrease:** Pour plenty of water and a little washing liquid onto a soft dishwashing sponge (without a scrubbing pad) or an eraser sponge and wipe over the sink in a circular motion. Rinse with plenty of clean water and then dry the sink with a soft microfiber cloth.

**Descale:** To remove stubborn limescale deposits, soap residue or gray haze, apply any mild descaler evenly to the affected surface and leave to work for 15 minutes. Then rinse with clean water and wipe dry. Repeat for stubborn limescale deposits.

**Deep Clean:** Pour approx. two centimeters of hot water (approx. 140°F) into the sink. Add one dishwasher tab or 2 tablespoons of a standard household dishwashing detergent to the hot water and stir well until the tab is clearly dissolved (caution: risk of scalding). You can apply a generous amount of the cleaning solution to the draining board or the edge of the sink using a dishwashing brush. Allow the lye to run off after 90 minutes and rinse the entire surface with plenty of cold water. If necessary, use the damp eraser sponge to remove any remaining residue. Then rinse well again, wipe the sink with a dry, soft cloth and leave to dry for at least 30 minutes.

**Sealing:** The sink must be completely clean and dry before sealing. Cover the parts not to be treated with a film and apply a sealant (approved for kitchen and bathroom sinks) as thinly and evenly as possible. It is best to apply a small amount of sealant to the surfaces to be treated and spread carefully with a clean fleece or microfiber cloth. After 1 minute, remove any excess sealant with a dry fleece or microfiber cloth. The product must be completely absorbed, it must not come to a standstill on the surface. The freshly treated sink should be protected from moisture for at least 6 hours, after which it is ready for use again.

**Please do not use any highly abrasive cleaning agents such as scouring agents, chlorine-based cleaners, drain cleaners or alkaline solutions and other solvents - these can cause lasting damage to your sink. You can easily keep your Pelican sink hygienically clean and remove even stubborn stains with mild cleaning and care products.**